We Claim:

1

2

4.

1	1. A method of scaling digital video information, said method
2	comprising:
3	accepting a scaling relaxation value, said scaling relaxation value specifying an
4	amount to relax a scaling performed to prevent buffer underflow or overflow;
5	and
6	adjusting a scaling value with said scaling relaxation value.
1	2. The method of scaling digital video information as claimed in
2	claim 1, said method further comprising:
3	calculating said scaling value, said scaling value dependent on a current buffer
4	usage.
1	3. The method of scaling digital video information as claimed in
2	claim 1 wherein said adjusting a scaling with said scaling relaxation value comprises
3	adding said scaling relaxation value to said scaling value and subtracting the product of
4	said scaling value and said scaling relaxation value.

DHJ --26-- APLE.P0036

claim 2 wherein said adjusting a scaling of a bit budget with said scaling relaxation value

The method of scaling digital video information as claimed in

- 3 comprises adding said scaling relaxation value to said scaling value and subtracting the
- 4 product of said scaling value and said scaling relaxation value.
- 1 5. A method of tracking digital video information complexity, said 2 method comprising: determining a complexity measure for a current digital video picture; and 3 combining said complexity measure for said current digital video picture to a 4 5 running average complexity measure for a series of digital video pictures in a 6 manner that prevents said current digital video picture from significant 7 changing said running average complexity measure for a series of digital video 8 pictures.

- 1 6. The method of tracking digital video information complexity as
 2 claimed in claim 5 wherein said running average complexity is not allowed to change by
 3 more than a predetermined percentage.
- 7. The method of tracking digital video information complexity as claimed in claim 5 wherein said running average complexity is processed by a non-linear smoothing filter.

DHJ --27-- APLE.P0036

1	8. A computer-readable medium comprising a set of computer
2	instructions for implementing a method of scaling digital video information, said set of
3	computer instructions performing:
4	accepting a scaling relaxation value, said scaling relaxation value specifying an
5	amount to relax a scaling performed to prevent buffer underflow or overflow;
6	and
7	adjusting a scaling value with said scaling relaxation value.
1	9. The computer-readable medium as claimed in claim 8 wherein said
2	set of computer instructions further perform:
3	calculating said scaling value, said scaling value dependent on a current buffer
4	usage.
1	10. The computer-readable medium as claimed in claim 8 wherein said
2	adjusting a scaling with said scaling relaxation value comprises adding said scaling
3	relaxation value to said scaling value and subtracting the product of said scaling value
4	and said scaling relaxation value.

DHJ --28-- APLE.P0036

adjusting a scaling of a bit budget with said scaling relaxation value comprises adding

said scaling relaxation value to said scaling value and subtracting the product of said

1

2

3

4

11.

scaling value and said scaling relaxation value.

The computer-readable medium as claimed in claim 9 wherein said

12. A computer-readable medium comprising a set of computer
instructions for tracking digital video information complexity, said set of computer
instructions performing:
determining a complexity measure for a current digital video picture; and
combining said complexity measure for said current digital video picture to a
running average complexity measure for a series of digital video pictures in a
manner that prevents said current digital video picture from significant
changing said running average complexity measure for a series of digital video
pictures.

5

6

8

9

- 1 13. The computer-readable medium as claimed in claim 12 wherein said running average complexity is not allowed to change by more than a predetermined percentage.
- 1 14. The computer-readable medium as claimed in claim 12 wherein 2 said running average complexity is processed by a non-linear smoothing filter.